

## Specification Data Sheet

### Prestige Oak 190 x 14/2 mm. Tongue & Groove (T&G) and Click.

**Prestige Oak** planks are manufactured with a **2mm solid European Oak wear layer** permanently bonded to a **12mm** mixed hardwood plywood substrate. This trusted method of construction provides a long wearing, stable and durable floor with a finished thickness of **14mm**. Ideal for floors, ceilings & walls in residential, multi-residential and commercial construction projects. **Interior use only.**

**Key Features;** Engineered to exacting standards. Manufactured from sustained yield forest resources. Extremely stable with excellent wear resistance. Wear layer can be re-sanded and rejuvenated throughout the products lifecycle.

**Colour Range;** Natural oak, light Scandinavian tones, warm, earthy greys to darker colours.

**Custom colours;** Contract colours for multi-residential or commercial projects by arrangement, minimum volume requirements will apply.

**Description;** Engineered European Oak, T&G for direct fix, trowel adhesive installation or **Click** profile for floating installation.

**Grade & Surface;** A/B/C/D Grade contains knots and split defects that are filled and patched to compliment surface colour and character. Pre-finished Matte, German PU coating. Light wire brushed surface.

**Size & Length;** 190mm width, 15mm thickness, 1900mm length, approx. 20% nested shorter planks, 2 rows / carton, balance set length.

**Quantity;** 2.166m<sup>2</sup> / carton, approx. 72 cartons / pallet.

**Profile;** Tongue & Groove (T&G) or **Click**, Unilin Angle to Angle profile. Micro Bevelled Edges.

**Acoustic outcome;** Test Result with 2mm Underlay, L'nT,w **42**.

**Fire Test Data;** AS/ISO9239.1-2003 (Flooring use) Critical Heat Flux, **3.7kW/m<sup>2</sup>**. Mean Smoke Development, **21 percent minutes**.

**Slip Resistance;** In accordance with AS/NZS 4586; 2013 **P3**. **VOC Emissions;** E1, (Below World Health Organisation Levels).

**R-Value Thermal Resistance;** **0.0875**. **JANKA Hardness;** 5.5 – 6.0kN.

**Accessories;** Alloy trims, MDF coloured scotia & Stair Nosing available to support colour selection for interior fit-out.

**Pre-finished, quick, and easy to lay - no dust, no smell, and no mess.** Please consult with your supplier for specific site install guidelines prior to installation. For specification or reseller support contact, [info@preferencefloors.com.au](mailto:info@preferencefloors.com.au) or a local sales office.

[www.preferencefloors.com.au](http://www.preferencefloors.com.au)

#### Adelaide (SA)

t +61 8 8262 2774  
sa@preferencefloors.com.au

#### Brisbane (QLD)

t +61 7 3875 1688  
qld@preferencefloors.com.au

#### Melbourne (VIC)

t +61 3 9794 5111  
vic@preferencefloors.com.au

#### Perth (WA)

t +61 8 9471 7785  
wa@preferencefloors.com.au

#### Sydney (NSW)

t +61 2 9738 1188  
sales@preferencefloors.com.au